



Type	Displacement cm <sup>3</sup> /rev	Flow		Pressure P <sub>nom</sub> bar	max Speed n rpm	Dimension							
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet		
								E	F	d	E	F	d
20A(C)4,5X647	4,5	6,14	14,33	250	3500	42	79,6	30,2	13,1	M6-6H	30,2	13,1	
20A(C)6,3X647	6,3	8,69	20,29	250	3500	43,6	82,6						
20A(C)8,2X647	8,2	11,32	26,40	250	3500	45	85,6						
20A(C)10X647	10	13,95	32,55	250	3500	46,6	88,7						
20A(C)11X647	11,3	15,76	36,78	250	3500	47,6	90,7						
20A(C)12X647	12	16,92	39,48	250	3500	48,2	91,9	39,7	19	M8-6H	30,2	14,2	M6-6H
20A(C)14X647	14	19,95	46,55	250	3500	49,6	95						
20A(C)15X647	15	21,60	36,00	250	2500	50,6	96,5						
20A(C)16X647	16	23,04	38,40	250	2500	51,6	98,2						
20A(C)19X647	19	27,36	45,60	200	2500	53,6	103,1						
20A(C)22X647	22	31,68	42,24	180	2000	56,6	108,1	39,7	19	M8	39,7	19	M8
20A(C)25X647	25	36,00	48,00	160	2000	58,8	113						