



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension							
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet				Outlet	
						F1	d	H1	L1	F2	d	H2	L2
30A(C)25X584H	25	35,3	70,5	250	3000	58,3	121,1						
30A(C)28X584H	28	39,5	79,0	250	3000	60,2	124,7						
30A(C)32X584	32	45,1	75,2	250	2500	62,0	128,3						
30A(C)32X584H	32	45,1	90,2	250	3000	66,5	137,3						
30A(C)36X584	36	50,8	84,6	250	2500	63,5	131,4						
30A(C)36X584H	36	51,3	95,8	250	2800	68,0	140,5						
30A(C)42X584	42	59,9	91,8	230	2300	66,3	137,0						
30A(C)42X584H	42	59,9	99,8	230	2500	70,8	146,1						
30A(C)46X584H	46	65,6	100,5	230	2300	72,7	149,8						
30A(C)50X584H	50	71,3	99,8	200	2100	74,5	153,4						
30A(C)55X584H	55	78,4	91,4	200	1750	76,7	157,9						
30A(C)60X584H	60	85,5	99,8	180	1750	78,7	162,4						